

**Applications:**

- Poultry houses
- Pig farms
- Equestrian centres
- Veterinary recovery surgeries
- Animal shelters
- Garden centres

**General Information:**

- Low energy consumption
- Soft light output
- Expected lamp life 40,000 hours
- Instant start
- Dimmable using trailing edge
- Lamp range – 25 watts
- Optimum installation height range (2.3 - 4 metres)
- Acrylic body
- IP67
- Mounting: surface, cable tied or clip for winching system

**Technical Information:**

- 100~277 Vac 50Hz
- 110Lm/W (Lumen/Watt)
- Colour Rendering Index (CRI) (Ra) => 78
- Lamp colour – Cool white 4000K
- Operating temperature -30°C to +40°C
- Power Factor => 0.95
- LED beam angle 180°

## LED Linear IP67 Dimmable



Available in 1200mm. IP67 cool white LED. Easy installation with plug connectors, patent registered Multi-fix system. Pre-wired cables with 1 m flex at each end. Single end light is pre-wired with 0.5 m flex.



All dimensions shown are in millimetres

### LED Linear IP67

Product Code	Description	Colour	Colour Temp (CCT)	Colour Rendering Index	Manufacturer's Av. Lifetime Expectancy	Lumens +/- 10%	Efficacy (lm/w)
LSL LSD LL 25 A	1.2m single end connection 25 W	Cool white	4000 K	78 Ra	40,000 hrs	2750	110
LSL LSD LL 25 B	1.2m dual end connection 25 W	Cool white	4000 K	78 Ra	40,000 hrs	2750	110
LSL LSD LL UC	Universal clip 26mm - 32mm diameter						

**LSLCo UK Ltd.**

Unit 13, Hazeley Enterprise Park, Hazeley Road, Twyford, Winchester. SO21 1QA, U.K.

Tel: +44 (0)1962 600 136 Web: [www.lslco.co.uk](http://www.lslco.co.uk) Email: [office.admin@lslco.co.uk](mailto:office.admin@lslco.co.uk)